THE COMMISSIONER OF PATENTS AND TRADEMARKS Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of:

INVENTOR: DAVID GOODNOUGH ET AL.

FOR: SYSTEM AND METHOD FOR ON-LINE SELECTION OF AN AIR CONDITIONING PRODUCT

(xxx)	COMBINED DECLARATION AND POWER OF ATTORNEY (INFORMAL) AND APPENDIX A.
()	Verified statement(s) to establish small entity status under 37 CFR 1.9 and 37 CFR 1.27.
()	A certified copy of Application No, Filed
()	An Assignment of the invention to
(FUCTO)	sheets of drawing(s).

The filing fee has been calculated as shown below:

			SMALL	SMALL ENTITY		OTHER THAN A SMALL ENTITY	
For	No. Filed	No. Extra	Rate	Fee	Rate	Fee	
Basic Fee				\$ 380		\$ 690	
Total Claims	16 - 20	= 0	x 9	\$	x 18	\$	
Indep Claims	1 - 3		x 39	\$	x 78	\$	
	e Dependent Presented	Claim	+135	\$	+270	\$	
			TOTAL	\$	TOTAL	\$ 690	

- (XX) Please charge my Deposit Account No. 02-0184 in the amount of 690.00. A duplicate copy of this sheet is enclosed.
-) A check in the amount of \$___ to cover the filing fee.
- (XX) The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 02-0184. A duplicate copy of this sheet is enclosed.
 - (x) Any additional filing fees required under 37 CFR 1.16.
 - (x) Any patent application processing fees under 37 CFR 1.17.
- (XX) The Commissioner of hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 02-0184. duplicate copy of this sheet is enclosed.
 - (x) Any patent application processing fees under 37 CFR 1.17.
 (x) Any filing fees under 37 CFR 1.17 presentation of extra claims.

January 28, 2000 EXPRESS MAIL #EL394338929US hareby certify that this correspondence is being desosited with the United States Postal Service es Express Mail in an envelope addressed to: Commissioner of Patents and Trademarks, Washington, D.C. 20239

January 28, 2000 Janice^{(D}T. o'Station of Signature

GRORGE A. COURY Attorney for Applicants Bachman & LaPointe, P.C. Suite 1201-900 Chapel Street New Haven, CT 06510-2802 Telephone: (203) 777-6628

SYSTEM AND METHOD FOR ON-LINE SELECTION OF AN AIR CONDITIONING PRODUCT

Technical Field

The invention relates to a system and method for on-line selection of a product and, more particularly, to an interactive system and method for on-line selection and purchase of an air conditioning product.

Background of the Invention

A portion of the disclosure of this document contains material which is subject to copyright protection. The copyright owner has no objection to the reproduction by anyone of the patent document or the patent disclosure as it appears in the Patent Office file, but otherwise reserves all copyright rights whatsoever.

Air conditioning products are widely used for conditioning the environment in enclosed areas. For example, room air conditioning products are used for cooling, and in some cases for heating, various enclosed areas such as rooms in a home and the like. Selection of a proper room air conditioning product for a particular intended use should take into account a number of factors related to the intended use location or environment. Unfortunately, consumers frequently select an air conditioning product without considering such factors.

One important characteristic of different air conditioning products is cooling and/or heating capacity. This capacity is typically measured in British Thermal Units or BTUs. A BTU is the amount or quantity of heat required to raise the temperature of 1 lb. of water by 1°F. As it applies to an air conditioning product, this product can be described as having a capacity in terms of BTUs output per hour.

An air conditioning unit should be selected to have a BTU capacity appropriate for the environment in which it will be

used. An air conditioning unit having a BTU capacity lower than is required for cooling a particular space and environment would run continuously and would not adequately cool the room. Conversely, an air conditioning product that has a BTU capacity higher than is required will cycle on and off frequently and will not properly dehumidify the environment of use.

A wide variety of different factors to consider when selecting a product having the appropriate capacity are known to the skilled technician in the air conditioning industry. However, such a technician may not routinely be available to a consumer selecting an air conditioning product. Thus, the need exists for an improved system and method by which consumers can select an appropriate air conditioning product for their intended use.

It is therefore the primary object of the present invention to provide such a system and method.

It is a further object of the present invention to provide a system and method for assisting a consumer in selecting an air conditioning product which is interactive and available on-line or by Internet.

Other objects and advantages of the present invention will appear hereinbelow.

SUMMARY OF THE INVENTION

In accordance with the present invention, the foregoing objects and advantages have been readily attained.

In accordance with the present invention, an interactive method for on-line selection of an air conditioning product is provided, comprising the steps of providing a database storing a plurality of air conditioning product identifiers and at least one corresponding product characteristic; interactively obtaining intended use information from a consumer for a desired air conditioning product and intended use location; equating

said intended use information with an intended use product characteristic; identifying a suitable product having said at least one product characteristic meeting said intended use product characteristic; and identifying said suitable product to said consumer. Preferably, the characteristic is BTU capacity.

In further accordance with the present invention, one or more types of further intended use location information may be interactively obtained from a consumer and used to determine a correction factor or factors and a corrected acceptable BTU capacity for a desired air conditioning product.

DETAILED DESCRIPTION

The invention relates to a system and method for interactively selecting an air conditioning product. More particularly, the invention relates to a system and method for selecting such an air conditioning product on-line or via the Internet or World Wide Web.

As is well known to a person of ordinary skill in the art, many on-line applications, Internet web pages and/or sites provide consumer accessible content such as product data and the like. Typically, the consumer is acting through a "client" computer system which accesses a "server" computer or computer system or network, whereby information is passed back and forth for a desired purpose. The specific technology for creating and operating such a system is well known to a person of ordinary skill in the art.

In accordance with the present invention, a server is established and programmed to interact with a consumer so as to assist in the proper selection and purchase of an air conditioning product which is appropriate for the consumer's intended use location. The thrust of the system and method is to guide a consumer through selection of an air conditioning

product having an acceptable BTU capacity for the intended use location.

Air conditioning products include a wide variety of products such as room air conditioners, humidifiers, dehumidifiers, purifiers and the like. Each of these types of air conditioning products should be selected taking into account a number of factors related to the intended use environment. The following description will be given as the invention relates to proper selection of a room air conditioner and the factors related thereto. It should of course be appreciated that the invention applies equally to other air conditioning products as well such as identified above, each of which has potentially the same or different intended use factors to consider.

As will be discussed more thoroughly below, the consumer selecting an air conditioning product is asked to input certain intended use information which is then utilized to determine an initial BTU capacity and one or more correction factors to be applied to the initial acceptable BTU capacity so as to determine a corrected acceptable BTU capacity for the consumer's desired location. A specific product which possesses a BTU rating meeting the corrected acceptable BTU capacity is then identified and offered for sale to the consumer. In accordance with the invention, the consumer may then proceed to purchase such product. An example of a suitable algorithm for carrying out the method of the invention is attached as Appendix A.

This method is preferably carried out via the Internet with the consumer receiving and providing information through a client computer to a server computer or network of computers programmed with the relevant air conditioning product information and selection algorithm. Alternatively, the software may be provided to consumers for installation on a consumer accessible personal computer, with the program interacting with the consumer to guide proper selection. This

mode of operation is specifically included within the term "on-line" as used herein.

In accordance with the method of the present invention, the proposed capacity of an air conditioning product for a specific desired location is determined in terms of capacity per hour, and will be referred to herein in specific units of British Thermal Units or BTU's per hour. It is of course to be understood that different systems of measurement are available for measuring capacity of an air conditioning product, and such capacity measuring systems are considered to be equivalent to and/or interchangeable with the BTUs discussed herein.

The method of the present invention is typically carried out by a computer or network of computers which functions as a consumer-accessible server. The server preferably includes a database storing a plurality of air conditioning product identifiers and at least one corresponding product characteristic. The server is also preferably programmed with a selection algorithm as discussed below which advantageously interacts with a consumer so as to obtain intended use information for a desired air conditioning product and intended use location and to equate this information with a suitable product which is then offered to the consumer. Alternatively, this information and algorithm may be stored on a CD-ROM or other distributable storage mechanisms as discussed above.

The information to be stored at the server preferably includes a first table or relationship equating a square footage or area of space to be cooled with a corresponding initial acceptable BTU per hour. A typical relationship between area and cooling BTU capacity is set forth below in Table 1.

	TADLIL	
Sq. E	<u>t.</u>	BTU
100		5000
150		5000
151		6000
300		6000
301		8000
350		8000
351		8600
450		8600
451		10000
500		10000
501		12000
700		12000
701		14000
800		14000
801		15000
900		15000
901		18000
1300		18000
1301		21000
1450		21000
1451		24000
1700		24000

one or more tables each containing a series of product identifiers and corresponding BTU ratings. The relationship between capacity and specific product identifier may suitably be broken into several portions for example related to products having different additional features such as heating capability, window or wall mounting capabilities and the like. For example, these relationships may be divided into a first portion relating to air conditioning products that are window mount capable and can cool only, a second portion of air conditioning products which are wall mount capable and can cool only, and a third portion relating to air conditioning products which can both cool and provide supplemental heat. Typical examples of such tables or portions of the relationship discussed are set forth below in Tables 2, 3 and 4.

	
• BTU	Product Identifier
3000 to 5200	UCA051B
	TCA051B
	TCB051B
5201 to 7000	LCA061P
	UCB061B
	TCA061D
	PCA061D
7001 to 9000	UCD081B
	TCA081D
	TCA081P
	53SSB009-1
	mor 101D
9001 to 11000	TCA101D
	GCA101B
11001 to 13000	TCA121D
11001 60 13000	GCA121B
	GCA123B
	XCB121E
	XCB121B XCB121R
	462AJC012BA
	DCA131G
	DOATOIG
13001 to 14000	DCA141D
10001 30 1111	
14001 to 16500	DCA153D
	462AJC015BA
16501 to 19000	XCB183D
	XCB183E
	462AJC015BA
	D 0 7 0 1 0 D
19001 to 22000	DCA213D
	YCA213R
	YCB213E
	462AJC021BA
22001 to 25000	JCA243D
ZZ001 CO Z3000	00/12400

3000 BTU 5200	Product Identifier UCA051B
5201 to 7000	UCB061B
7001 to 9000	UCD081B
9001 to 11000	GCA101B
11001 to 13000	GCA121B GCA123B XCB121E XCB121R 462JC012BA DCA 131G
13001 to 14000	DCA141D
14001 to 16500	DCA153D 462AJC015BA
16501 to 19000	XCB183D XCB183E 462AJC018BA
19001 to 22000	DCA213D YCA213R 462AJCO21BA YCB213E
22001 to 25000	JCA243D

3000 ETU 5200	Product Identifier N/A
5201 to 7000	N/A
7001 to 9000	N/A
9001 to 11000	XHC101D XQB101D
11001 to 13000	XHA123D XQA123D
13001 to 14000	XHA123D XQA123D
14001 to 16500	XHB153D XQB153D
16501 to 19000	XHB183D XQB183D
19001 to 22000	YHB243D
22001 to 25000	YHB243D

The server database is further preferably programmed to store the selection algorithm and/or several correction factors for use by the algorithm which are used along with information obtained from the consumer and the initial capacity from Table 1 to obtain a corrected acceptable product capacity. This corrected capacity is then used with tables such as Tables 2-4 to identify a suitable product. The selection algorithm and various correction factors will be discussed in detail below. In addition, Appendix A annexed hereto contains a non-limiting example of a specific embodiment of a selection algorithm according to the invention.

Once a consumer has accessed the server for carrying out the method of the present invention, the consumer is asked to enter the dimensions of the intended use location or room. This

area is calculated at the server from room dimensions entered by the consumer. 'Alternatively, the area may be directly entered by the consumer. Areas are referred to herein in units of square feet. Of course, other systems of measurement can be used.

In accordance with the invention, the area is then checked against an area to capacity table such as Table 1 to insure that the information stored in the database can help to select the proper air conditioning product. If the area entered by the consumer exceeds the maximum area in the stored area to initial capacity relationship or table, the consumer can preferably be instructed to contact a local dealer for further assistance with unit selection.

Assuming that the consumer input area is located in the area to initial capacity table, the initial capacity value from the table is assigned by the server to an intermediate identifier of the algorithm such as "BTU 1".

The consumer is then asked to input the area of glass at the intended use location or room which faces the exterior or outdoors. This information to be input should include the area of windows, skylights, glass doors and the like, each of which can add to the required capacity for an air conditioning product suitable for that particular intended use location. The server is preferably programmed to store a correction factor or relationship to correct for the consumer identified exterior facing glass.

For example, the exterior glass area may be used to determine a corrected capacity as follows:

 $R_C = R_I + (C \cdot 60)$, wherein

 $\ensuremath{\text{R}_{\text{I}}}$ is an initial acceptable product capacity in BTU/hour,

 R_{c} is a corrected acceptable capacity in BTU/hour, and

C is exterior glass area in square feet.

above may be capacity determined from the area to initial capacity table (BTU 1), or may be an intermediate corrected capacity already corrected for other factors such as those discussed below. Further, the corrected capacity $R_{\rm C}$ may suitably be utilized to select an appropriate product, or may be used as a starting point for other correction determinations. For example, the value of $R_{\rm C}$ from this step may be assigned to a further intermediate algorithm identifier such as "BTU 2" which is then utilized in subsequent steps to obtain a further corrected rating or capacity. Thus, the term 'initial' as used herein in connection with product capacities and BTU capacities specifically includes, without limitation, intermediate capacities obtained from other correction determinations.

According to the invention, the consumer is next asked to indicate whether the intended use location or room is normally in the sun or shade. Depending upon the answer entered, the server is preferably programmed to carry out a further correction. For example, a corrected capacity may be determined as follows:

If "sun" then $R_C = R_I \cdot 1.1$, and

If "shade" then $R_C = R_I \cdot 0.95$, wherein

 $\ensuremath{R_{\mathrm{I}}}$ is an initial or intermediate acceptable capacity in BTU/hour, and

 R_{c} is a corrected product capacity in BTU/hour.

The value R_{C} obtained from this calculation may suitably be used to select a product or may be assigned to a value "BTU 3" for further use in the selection algorithm. Further, the value R_{I} may be the value "BTU 2" which is obtained following the consumer input of exterior glass area.

The consumer is then preferably asked to enter whether the space above the room is a roof only, an attic or an occupied

room. With this information, a further corrected acceptable product capacity is determined, for example as follows:

If roof only, then $R_C = R_I$

If attic, then $R_C = R_I \cdot 0.85$, and

If occupied room, $R_C = R_I \cdot 0.8$, wherein

 $\ensuremath{R_{\text{I}}}$ is an initial or intermediate acceptable capacity in BTU/hour, and

 $\ensuremath{R_\text{C}}$ is a corrected product capacity in BTU/hour.

The corrected BTU capacity may then be used to select a product or may be assigned to a new algorithm identifier "BTU 4" for use in subsequent steps.

The consumer is then preferably asked to input whether the intended use location is above a cooled space such as a basement or another air-conditioned room, and a further corrected product rating is determined, for example as follows:

If above cooled space, then $R_C = R_I \cdot 0.8$, and

If not above cooled space, then $R_{\text{C}} = R_{\text{I}} \cdot 0.9$, wherein

 $\ensuremath{R_\mathrm{I}}$ is an initial or intermediate acceptable product capacity in BTU/hour, and

 R_{C} is a corrected acceptable product capacity in BTU/hour.

The corrected product capacity determined from this step may be used to select a product or can be assigned to an identifier "BTU 5" for further use by the selection algorithm.

The consumer is then asked to enter whether the desired product will be operated only at night which can affect the appropriate product capacity significantly. The method of the present invention then determines a further corrected acceptable capacity using this information, for example as follows:

If night only, then $R_C = R_I \cdot 0.65$, and Otherwise, $R_C = R_I$, wherein

 $\ensuremath{R_\text{I}}$ is an initial or intermediate acceptable product capacity in BTU/hour, and

 R_{C} is a corrected product capacity in BTU/hour.

The corrected product capacity obtained from this step may be used to select a suitable product or can be assigned to a further algorithm identifier "BTU 6".

The consumer is then asked to input a geographic location indicator which serves to identify the area where the desired product is to be used. Preferably, this indicator will be entered in the form of a postal zip code, although other methods can be used such as telephone area code and the like. In further accordance with the present invention, the server may advantageously be programmed to store a correlation of climate correction factors corresponding to zip codes or other geographic indicators and designed to suitably correct a product capacity for the specific climate of a geographic location of intended use. A portion of a typical correlation between zip code and climate factor is set forth below in Table 5.

TABLE	5
-------	---

ZIP CODE	CLIMATE
12000	0.7
12999	0.7
13000	0.8
14999	0.8
15000	0.8
15999	0.8
16000	0.9
17999	0.9
18000	0.8
18999	0.8
19000	0.9
19999	0.9
20000	1
20099	1
20100	0.9
20999	0.9

In accordance with the method of the present invention, a further corrected acceptable product capacity is determined using the climate correction factor, for example as follows:

 $R_C = R_I \cdot CF$, wherein

 $R_{\text{\scriptsize I}}$ is an initial or intermediate acceptable product capacity in BTU/hour,

 $\ensuremath{R_\text{C}}$ is a corrected acceptable product capacity in BTU/hour, and

CF is a climate factor obtained as in Table 5.

The value of the corrected product capacity obtained in this step may be used to select a product or can be assigned to a further algorithm identifier "BTU 7".

The consumer is next asked to identify the number of people who normally occupy the room or intended use location. From this information, a further corrected acceptable product capacity is determined for example as follows:

$$R_C = [(I -2) \cdot 600] + R_I$$
, wherein

 $\ensuremath{\mathtt{R}}_{\mathtt{I}}$ is an initial or intermediate acceptable product capacity in BTU/hour,

 R_{C} is a corrected acceptable product capacity in BTU/hour, and

I is the number of people entered by the consumer.

The corrected product capacity determined from this step may be used to select a product or can be assigned to a further algorithm identifier "BTU 8".

The consumer is preferably next asked to indicate whether the intended use location includes a kitchen, and a further corrected acceptable product capacity is determined based on this input, for example as follows:

If kitchen, then $R_C = R_I + 4,800$, and Otherwise, $R_C = R_I + 300$, wherein

 $\ensuremath{R_{\text{I}}}$ is an initial or intermediate acceptable product capacity in BTU/hour, and

. R_{C} is a corrected acceptable product capacity in BTU/hour. The value of the corrected acceptable capacity determined in this step may be used to select a product or can be assigned

to a further algorithm identifier "BTU 9".

The consumer may then preferably be asked to indicate whether the desired unit will be installed in a window or through a wall, and further whether the desired product must be capable of cooling and supplemental heating, or of cooling only. The information entered by the consumer at this step can be used to determine which table or portion of the relationship or table of acceptable BTU capacity to product identifier (Table 2, 3 and 4) to be used to identify a suitable product for the consumer.

For example, assuming use of all of the correction factors identified above, and use of Tables 2-4, if the consumer enters that the desired product is to be window mounted and need not have heating capacity, the suitable product would be selected from Table 2 using the value "BTU 9". If the consumer enters that the product is to be mounted through a wall and need not have heating capacity, a suitable product could be selected from Table 3 using the value "BTU 9". If the consumer indicates that the desired product must be capable of heating, a suitable product can be selected from Table 4 using the value "BTU 9", and if a window-mount is indicated as desired, the consumer could be advised to also purchase a window installation kit.

As shown in Tables 2-4, the product characteristic is preferably BTU rating for each product available. Once a corrected acceptable BTU capacity has been determined, a product having a BTU rating meeting the corrected acceptable BTU capacity is selected at the server from the appropriate table and identified to the consumer at the client machine. For example, if a consumer has indicated a wall mounted "cooling only" unit and information leading to a corrected acceptable BTU capacity of 4,100 BTU/hour, Table 3 would be used to select

product identifier UCA051B corresponding to a wall mountable unit having a rating of 3,000-5,300 BTU/hour. Thus, the product characteristic is preferably a range representing capability of a particular product and the intended use product characteristic is a value, preferably corrected for various intended use factors, which can be compared or matched to the stored product characteristic ranges to identify a suitable product.

As set forth above, a series of correction steps or factors are identified for determining a corrected acceptable product capacity from an initial acceptable product capacity. A preferred embodiment of the present invention would include a series of correction factor determinations wherein the value BTU 1 identified above is assigned as the initial capacity for the next step, and so on, so as to obtain a final corrected acceptable product capacity which takes each factor into account. Through this method, a consumer is interactively guided to the selection of an ideal product for a specific intended use location, thereby avoiding problems inherent with use of air conditioning products having ratings too low or high for a desired intended use location.

The method of the present invention interacts with the consumer, asking that information be entered at the client machine by the consumer, and responding to entry with further information requests and/or identification of a suitable product from the server machine or network.

Thus, consumer guidance is provided in a readily available manner thereby greatly increasing accessibility of critical information for use in selecting an appropriate air conditioning product.

It should be readily appreciated that the foregoing specific steps provide a detailed description of a preferred method for carrying out the present invention. It should also be appreciated that a number of other correction factors, or a

combination of some but not all of those factors discussed above could be assembled, all well within the scope of the present invention.

It should also be appreciated that this disclosure provides a method whereby a consumer can access a system by Internet for interactively guiding the selection of an appropriate product, whereby selection of an appropriate product based upon industry expertise is significantly more convenient for the consumer.

It is to be understood that the invention is not limited to the illustrations described and shown herein, which are deemed to be merely illustrative of the best modes of carrying out the invention, and which are susceptible of modification of form, size, arrangement of parts and details of operation. The invention rather is intended to encompass all such modifications which are within its spirit and scope as defined by the claims.

WHAT IS CLAIMED IS:

1. An interactive method for on-line selection of an air conditioning product, comprising the steps of:

providing a database storing a plurality of air conditioning product identifiers and at least one corresponding product characteristic;

interactively obtaining intended use information from a consumer for a desired air conditioning product and intended use location;

equating said intended use information with an intended use product characteristic;

identifying a suitable product having said at least one product characteristic meeting said intended use product characteristic; and

identifying said suitable product to said consumer.

- 2. The method of claim 1, wherein said database is stored at a server location and wherein said intended use information is obtained from said consumer at a client location communicated with said server location by Internet.
- 3. The method of claim 1, wherein said identifying step further includes offering said product to said consumer for purchase.
- 4. The method of claim 1, wherein said corresponding product characteristic includes a BTU rating for each product of said plurality of product identifiers.
- 5. The method of claim 1, wherein said corresponding product characteristic includes a BTU rating for each product, and wherein said step of interactively obtaining comprises:

, obtaining intended use location area from said consumer; transforming said intended use location area into an initial acceptable BTU capacity for said intended use location area;

obtaining further intended use location information from said consumer;

determining a correction factor from said further intended use location information; and

applying said correction factor to said initial acceptable BTU capacity so as to obtain a corrected acceptable BTU capacity, and wherein said equating step comprises identifying said suitable product having said BTU rating meeting said corrected acceptable BTU capacity.

6. The method of claim 5, wherein said further intended use location information includes an indication from said consumer as to area of exterior facing glass at said intended use location, and wherein said corrected acceptable BTU capacity is determined as follows:

 $R_C = R_I + (C \cdot 60)$, wherein

 $R_{\rm I}$ is said initial acceptable BTU capacity in BTU/hour, $R_{\rm C}$ is said corrected acceptable BTU capacity in BTU/hour and

C is said area of exterior facing glass in square feet.

7. The method of claim 5, wherein said further intended use location information includes an indication from said consumer as to whether said intended use location is in sun or shade, and wherein said corrected acceptable BTU capacity is determined as follows:

if sun, $R_C = R_I \cdot 1.1$; and

if shade, $R_C = R_I \cdot 0.95$; wherein

 $R_{\text{\tiny I}}$ is said initial acceptable BTU capacity in BTU/hour, and '

 R_{C} is said corrected acceptable BTU capacity in BTU/hour.

8. The method of claim 5, wherein said further intended use location information includes an indication from said consumer that a space above said intended use location is one of a roof, an attic, and an occupied room, and wherein said corrected acceptable BTU capacity is determined as follows:

if roof, $R_C = R_I$,

if attic, $R_C = R_I \cdot 0.85$, and

if occupied room, $R_C = R_I \cdot 0.8$, wherein

 $R_{\text{\tiny T}}$ is said initial acceptable BTU capacity in BTU/hour, and

 R_{c} is said corrected acceptable BTU capacity in BTU/hour.

9. The method of claim 6, wherein said further intended use location information includes an indication from said consumer as to whether said intended use location is above a cooled space, and wherein said corrected acceptable BTU capacity is determined as follows:

if above a cooled space, $R_C = R_I \cdot 0.8$, and

if not above a cooled space, $R_C = R_I \cdot 0.9$, wherein

 R_{I} is said initial acceptable BTU capacity in BTU/hour,

and

 $\ensuremath{R_{\text{C}}}$ is said corrected acceptable BTU capacity in BTU/hour.

10. The method of claim 5, wherein said further intended use location information includes an indication from said consumer as to whether said desired air conditioning product

will be operated only at night, and wherein said corrected acceptable BTU capacity is determined as follows:

if operated only at night, $R_C = R_I \cdot 0.65$, and otherwise, $R_C = R_I$, wherein

 $R_{\rm I}$ is said initial acceptable BTU capacity in BTU/hour, and

 R_{C} is said corrected acceptable BTU capacity in BTU/hour.

- 11. The method of claim 5, wherein said further intended use location information includes an indication from said consumer as to geographic location and wherein said step of determining said BTU correction factor includes determining a correction factor for said geographic location.
- 12. The method of claim 11, wherein said database stores a series of geographic location indicators and a series of correction factors corresponding to said geographic location indicators, and wherein said further intended use location information from said consumer includes a geographic location indicator.
- 13. The method of claim 12, further comprising the steps of determining an intended use location climate factor from said geographic location indicator, and determining a corrected acceptable product capacity as follows:

 $R_C = R_I \cdot CF$, wherein

 R_{I} is said initial acceptable BTU capacity in BTU/hour, R_{C} is said corrected acceptable BTU capacity in BTU/hour, and

CF is said intended use location climate factor.

. 14. The method of claim 5, wherein said further intended use location information includes a number of occupants of said intended use location, and wherein said corrected acceptable BTU capacity is determined as follows:

 R_{C} = [(I-2) X 60] + R_{I} , wherein R_{I} is said initial acceptable BTU capacity in BTU/hour, R_{C} is said corrected acceptable BTU capacity in BTU/hour, and I is said number of occupants.

15. The method of claim 5, wherein said further intended use location information includes an indication from said consumer as to whether said intended use location includes a kitchen, and wherein said corrected acceptable BTU capacity is determined as follows:

if kitchen, $R_C = R_I + 4,800$; and if no kitchen, $R_C = R_I + 300$; wherein R_I is said initial acceptable BTU capacity in BTU/hour, and R_C is said corrected acceptable BTU capacity in BTU/hour.

16. The method of claim 5, wherein said database stores a series of product identifiers and corresponding ranges of product BTU ratings, and wherein said series is divided into a first portion applicable to air conditioning products which only cool and which mount through a window, a second portion applicable to air conditioning products which only cool and which mount through a wall, and a third portion applicable to air conditioning products which cool and heat, wherein said further intended use location information includes an indication from said consumer as to whether said desired air conditioning product is to be mounted in a wall or a window, and whether said

desired air conditioning product must be able to cool and heat, and wherein said identifying step includes identifying said suitable product using said corrected acceptable BTU capacity and one of said first portion if said desired air conditioning product is to be mounted in a window and only cool, said second portion if said desired air conditioning product is to be mounted in a wall and only cool, and said third portion if said desired air conditioning product must cool and heat.

ABSTRACT OF THE DISCLOSURE

An interactive method for on-line selection of an air conditioning product includes the steps of providing a database storing a plurality of air conditioning product identifiers and at least one corresponding product characteristic; interactively obtaining intended use information from a consumer for a desired air conditioning product; equating the intended use information with an intended use product characteristic; identifying a suitable product having the at least one product characteristic meeting the intended use product characteristic; and identifying the suitable product to the consumer.

Practitioner's Docket No. 99-642 PATENT
COMBINED DECLARATION AND POWER OF ATTORNEY
(ORIGINAL, DESIGN, NATIONAL STAGE OF PCT, SUPPLEMENTAL, DIVISIONAL, CONTINUATION, OR C-I-P)
As a below named inventor, I hereby declare that:
TYPE OF DECLARATION
This declaration is of the following type:
(check one applicable item below)
₩ original.
design.
supplemental.
NOTE: If the declaration is for an International Application being filed as a divisional, continuation or continuation-in-part application, do not check next item; check appropriate one of last three items.
☐ national stage of PCT.
NOTE: If one of the following 3 items apply, then complete and also attach ADDED PAGES FOR DIVISIONAL, CONTINUATION OR C-I-P.
NOTE: See 37 C.F.R. § 1.63(d) (continued prosecution application) for use of a prior nonprovisional application declaration in the continuation or divisional application being filed on behalf of the same or fewer of the inventors named in the prior application.
☐ divisional.
☐ continuation.
NOTE: Where an application discloses and claims subject matter not disclosed in the prior application, or a continuation or divisional application names an inventor not named in the prior application, a continuation-in-part application must be filed under 37 C.F.R. § 1.53(b) (application filing requirements—nonprovisional application).
☐ continuation-in-part (C-I-P).
INVENTORSHIP IDENTIFICATION
WARNING: If the inventors are each not the inventors of all the claims, an explanation of the facts, including

WARNING: If the inventors are each not the inventors of all the claims, an explanation of the facts, including the ownership of all the claims at the time the last claimed invention was made, should be submitted.

My residence, post office address and citizenship are as stated below, next to my name. I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter that is claimed, and for which a patent is sought on the invention entitled:

TITLE OF INVENTION

SYSTEM AND METHOD FOR ON-LINE SELECTION OF AN AIR

CONDITIONING PRODUCT

(Declaration and Power of Attorney [1-1]-page 1 of 7)

SPECIFICATION IDENTIFICATION

the specification of which:

(Rel.79—4/99 Pub.605)

(complete (a), (b), or (c))

(a) AA IS	attached hereto.
filing o with a	following combinations of information supplied in an oath or declaration filed on the application date with a specification are acceptable as minimums for identifying a specification and compliance may one of the items below will be accepted as complying with the identification requirement of FR 1.63:
ti	(1) name of inventor(s), and reference to an attached specification which is both attached to ne oath or declaration at the time of execution and submitted with the oath or declaration on filling;
c	"(2) name of inventor(s), and attorney docket number which was on the specification as filed;
	"(3) name of inventor(s), and title which was on the specification as filed."
	Notice of July 13, 1995 (1177 O.G. 60).
	as filed on, as \square Serial No. 0 /
	d was amended on (if applicable).
NOTE: Amer not ac are ti amen	ndments filed after the original papers are deposited with the PTO that contain new matter are occorded a filing date by being referred to in the declaration. Accordingly, the amendments involved nose filed with the application papers or, in the case of a supplemental declaration, are those dments claiming matter not encompassed in the original statement of invention or claims. See
NOTE: "The	F.R. § 1.67. following combinations of information supplied in an eath or declaration filed after the filing date exceptable as minimums for identifying a specification and compliance with any one of the items will be accepted as complying with the identification requirement of 37 CFR 1.63:
	"(A) application number (consisting of the series code and the serial number, e.g., 08/123,456);
	"(B) serial number and filing date;
i.	"(C) attorney docket number which was on the specification as filed; "(D) title which was on the specification as filed and reference to an attached specification which is both attached to the oath or declaration at the time of execution and submitted with the oath or declaration; or
2	"(E) title which was on the specification as filed and accompanied by a cover letter accurately dentifying the application for which it was intended by either the application number (consisting of the series code and the serial number, e.g., 08/123,456), or serial number and filing date. Absenting statement(s) to the contrary, it will be presumed that the application filed in the PTO is the application which the inventor(s) executed by signing the cath or declaration."
	M.P.E.P. § 601.01(a), 7th Ed.
	as described and claimed in PCT International Application No.
ar	nended under PCT Article 19 on (if any).
	(Declaration and Power of Attorney [1-1]—page 2 of 7

FORM 1-1

SUPPLEMENTAL DECLARATION (37 C.F.R. § 1.67(b))
(complete the following where a supplemental declaration is being submitted)
☐ I hereby declare that the subject matter of the
attached amendment
amendment filed on
was part of my/our invention and was invented before the filing date of the original application, above-identified, for such invention.
ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR
I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information, which is material to patentability as defined in 37, Code of Federal Regulations, § 1.56,
(also check the following items, if desired)
and which is material to the examination of this application, namely, information where there is a substantial likelihood that a reasonable Examiner would consider it important in deciding whether to allow the application to issue as a patent, and
in compliance with this duty, there is attached an information disclosure statement, in accordance with 37 C.F.R. § 1.98.
PRIORITY CLAIM (35 U.S.C. §§ 119(a)-(d))
NOTE: "The claim to priority need be in no special form and may be made by the attorney or agent if the foreign application is referred to in the oath or declaration as required by § 1.63. The claim for priority and the certified copy of the foreign application specified in 35 U.S.C. 119(b) must be filed in the case of an interference (§ 1.630), when necessary to overcome the date of a reference relied upon by the examiner, when specifically required by the examiner, and in all other situations, before the patent is granted. If the claim for priority or the certified copy of the foreign application is filed after the date the issue fee is paid, it must be accompanied by a petition requesting entry and by the fee set forth in § 1.17(i). If the certified copy is not in the English language, a translation need not be filed except in the case of interference; or when necessary to overcome the date of a reference relied upon by the examiner; or when specifically required by the examiner, in which event an English language translation must be filed together with a statement that the translation of the certified copy is accurate." 37 C.F.R. § 1.55(a).
I hereby claim foreign priority benefits under Title 35, United States Code, §§ 119(a)–(d) of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed
below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.
below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date
below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.
below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed. (complete (d) or (e))

(Declaration and Power of Attorney [1-1]-page 3 of 7)

COUNTRY (OR INDICATE IF

PCT)

PRIOR FOREIGN/PCT APPLICATION(S) FILED WITHIN 12 MONTHS (6 MONTHS FOR DESIGN) PRIOR TO THIS APPLICATION AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. § 119(a)—(d)

APPLICATION NUMBER

DATE OF FILING PRIORITY CLAIMED UNDER 37 USC 119

				☐ YES	NO 🗆
				☐ YES	NO 🗆
				☐ YES	ио □
				☐ YES	NO 🗆
				☐ YES	№ □
l here	by clai	OR BENEFIT OF PRIOR (34 U.S. im the benefit under Title 33 anal application(s) listed belo	.C. § 119(e)) 5, United States		
		. APPLICATION NUMBER		FILING D	PATE
				•	
	/		*****		
		M FOR BENEFIT OF EAUNDER 35 The claim for the benefit attached ADDED PAGES TO ATTORNEY FOR DIVISION PART (C-I-P) APPLICATION	of any such app O COMBINED DE NAL, CONTINUAT	lications are set	forth in the
				ower of Attorney [1-1	i]—page 4 of 7)
(Rel.79-4/99	Pub.605)		FORM 1-1		1-8

ALL F	OREIGN APPLICATION(S), <i>IF ANY,</i> FILE (6 MONTHS FOR DESIGN) PRIOR TO TI	ED MORE THAN 12 MONTHS HIS U.S. APPLICATION
NOTE:	If the application filed more than 12 months from the filing of the basis for this application entering the United States as divisional, or continuation-in-part, then also complete ADI AND POWER OF ATTORNEY FOR DIVISIONAL, CONTIN- of the prior U.S. or PCT application(s) under 35 U.S.C. §	s (1) the national stage, or (2) a continuation, DED PAGES TO COMBINED DECLARATION UATION OR C-I-P APPLICATION for benefit
	POWER OF ATTORE	NEY
I here	eby appoint the following practitioner(s) to pros ness in the Patent and Trademark Office conn	secute this application and transact sected therewith.
Robert Kelmac	(list name and registration H. Bachman (19,374); Gregory P. LaF hter (29,999) and George A. Coury (3	Pointe (28,395); Barry L.
	(check the following item, if	applicable)
[I hereby appoint the practitioner(s) associate vided below to prosecute this application Patent and Trademark Office connected the	and to transact all business in the
[Attached, as part of this declaration and po of the above-named practitioner(s) to acce representative(s).	ower of attorney, is the authorization ept and follow instructions from my
SEND (CORRESPONDENCE TO	DIRECT TELEPHONE CALLS TO: (Name and telephone number)
1	Address BACHMAN & LAPOINTE, P.C. 900 Chapel Street Suie 1201 New Haven, CT 06510-2802	George A. Coury (203) 777-6628, Ext. 113
	☐ Customer Number	

(Declaration and Power of Attorney [1-1]-page 5 of 7)

(Rel.79-4/99 Pub.605)

DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SIGNATURE(S)

- NOTE: Carefully indicate the family (or last) name, as it should appear on the filing receipt and all other documents.
- NOTE: Each inventor must be identified by full name, including the family name, and at least one given name without abbreviation together with any other given name or initial, and by his/her residence, post office address and country of citizenship. 37 CFR § 1.63(a)(3).
- NOTE: Inventors may execute separate declarations/oaths provided each declaration/oath sets forth all the inventors. Section 1.63(a)(3) requires that a declaration/oath, inter alia, identify each inventor and prohibits the execution of separate declarations/oaths which each sets forth only the name of the

executing inventor. 62 Fed. Reg. 53,131, 53,142, October 10, 1997, Full name of sole or first inventor David Goodnough (GIVEN NAME) (MIDDLE INITIAL OR NAME) FAMILY (OR LAST NAME) Inventor's signature ___ _____ Country of Citizenship __ Date _ Residence . Post Office Address_ Full name of second joint inventor, if any Marv Burgess (GIVEN NAME) (MIDDLE INITIAL OR NAME) FAMILY (OR LAST NAME) Inventor's signature __ _____ Country of Citizenship __ Date _ Residence _ Post Office Address __ Full name of third joint inventor, if any Charles Bullock (GIVEN NAME) (MIDDLE INITIAL OR NAME) FAMILY (OR LAST NAME) Inventor's signature ___ Date _ ___ Country of Citizenship _ Residence _ Post Office Address _ (Declaration and Power of Attorney [1-1]-page 6 of 7)

FORM 1-1

1-10

(check	proper	box(es)	for any	of the	following	added	page(s)
	tř	at form	a part	of this	declaratio	n)	

Signature for fourth and subsequent joint inventors. Number of pages added

	* * *
	Signature by administrator(trix), executor(trix) or legal representative for deceased or incapacitated inventor. Number of pages added
	* * *
	Signature for inventor who refuses to sign or cannot be reached by person authorized under 37 CFR 1.47. Number of pages added
	• • •
	Added page for signature by one joint inventor on behalf of deceased inventor(s) where legal representative cannot be appointed in time. (37 CFR 1.47)
	• • •
	Added pages to combined declaration and power of attorney for divisional, continuation, or continuation-in-part (C-I-P) application. □ Number of pages added
	Authorization of practitioner(s) to accept and follow instructions from representative.
	• • •
;	(if no further pages form a part of this Declaration, then end this Declaration with this page and check the following item)
	☐ This declaration ends with this page.

(Declaration and Power of Attorney [1-1]—page 7 of 7)

ADDED PAGE TO COMBINED DECLARATION AND POWER OF ATTORNEY FOR SIGNATURE BY FOURTH AND SUBSEQUENT INVENTORS

Full name of fourth joint Rachel	inventor, if any	D al ton
(GIVEN NAME)	(MIDDLE INITIAL OR NAME)	FAMILY (OR LAST NAME)
Inventor's signature		
	Country of Citizenship	
Residence		
Post Office Address		
Full name of fifth joint in	nventor, if any	
(GIVEN NAME)	(MIDDLE INITIAL OR NAME)	FAMILY (OR LAST NAME)
Inventor's signature		
Date	Country of Citizenship	·
Residence		· · · · · · · · · · · · · · · · · · ·
Post Office Address		
Full name of sixth joint i	nventor, if any	
(GIVEN NAME)	(MIDDLE INITIAL OR NAME)	FAMILY (OR LAST NAME)
Inventor's signature		
Date	Country of Citizenship	·
Residence		
Doot Office Address		

Added Page to Combined Declaration and Power of Attorney for Signature by Fourth and Subsequent Inventors [1-2])

ALGORITHM - REV. D

SELECTING YOUR CARRIER ROOM AIR CONDITIONER

NOTE: IF THIS UNIT IS INTENDED FOR A SUN ROOM OR COMMERCIAL APPLICATION, PLEASE CONTACT YOUR LOCAL CARRIER DEALER

Drop Down

A. Length of room in feet		Drop Down 8 through 45		
B. Width of room in	ı feet			Drop Down 8 through 60
CALCULATE:	A x B = Sq. Ft. If Sq. Ft. \leq 1700, then GOTO BTU on this website. Please contact you selection."	J Table # our local C	1; Else ' Carrier d	"Your requirement cannot be satisfied lealer for further assistance with unit
LOOK-UP:	BTU Table # 1 and select BTU Siz BTU Size = BTU #1	ze based o	on Sq. F	t.
Total State	re feet of glass facing outdoors are in	the room	ı? (Rang	Drop Down e 10-100)
note: length in ft.	x width in ft. = sq. ft dows, skylights, and glass doors)		,	
CALCULATE:	BTU # 2 = BTU # 1 + (C x 60) NOTE: Round down for all fraction	ons.		
D. Is room normall CALCULATE:	ly in sun or shade? If "Sun," then BTU # 3 = BTU # If "Shade," then BTU # 3 = BTU	Sun_ 2 x 1.1 # 2 x .9 5		Shade
note: If only one e	xternal wall is in the sun, enter "Sl	hade."		
E. What type of sp	pace is above the room?	Roof	Only_	Attic Occupied Room
CALCULATE:	If roof only, then BTU #4 = BTU If attic, then BTU #4= BTU #3 x If occupied room, then BTU #4 =	.85	x .8	
F. Is room above of	cooled space (i.e. basement, another	air-condit	ioned ro	oom)? Yes No
CALCULATE:	If Yes, then BTU #5 = BTU #4 x If No, then BTU #5 = BTU #4 x	k .8 .9		

G. Will unit be operat	ted during the night only?		Yes	No
•	•			
	If Yes, then BTU # $6 = BTU # 5 \times .6$ If No, then BTU # $6 = BTU #5$	5		
H. Enter zip code who (note: zip codes are n Climate Factor	ere unit will be installednatched to factors to determine climat	e conditions in your	area of the	country)
CALCULATE:	BTU #7 = BTU #6 x climate facto	r		
LOOK-UP: Table a space above where it	A and select map factor based on corr says Climate Factor.	esponding zip code.	Map factor	r should appear in the
I. Number of people	who normally occupy room	Drop Down Range 2-8		
CALCULATE:	BTU # $8 = [(I-2) \times 600] + BTU # 7$	•		
J. Is the room a kitch	en?	Yes No		
CALCULATE:	If "Yes," then $BTU # 9 = BTU # 8$	+ 4,800		
já	Else,	,		
Hum dun	If "No," then BTU # 9 = BTU # 8 +	300		
K. Will the unit be in	nstalled in a window or through-the-v	vall? Window	Wall	
L. Do you require a	unit, which cools and heats?	Yes	No	
NOTE: THIS REQUIREMENTS ON	IS SUPPLEMENTAL HEAT. UNIT SEL LY!!!	ECTION WILL BE BA	ASED ON YO	OUR COOLING
COMPARE:	If BTU # 9 is $<$ 9001 and "L" = "Y	es," then provide a t	test window	as follows:
"At this time, Carrier able to satisfy your o	r does not offer a combination heat/co cooling requirements. Would you like Yes	ool unit that meets your ro to eliminate your ro No	our requiren equest for su	nents, though we are upplemental heat?"
	If "Yes," GOTO the Picture/Spec F			
	Else,	110.		
	If "No," provide a text window as f	follows:		
cooling/heating need	d on the information you have provid ds. For further assistance, please cont grequirements. Thank you."	ed, Carrier cannot ac act your local Carrie	ecommodate er dealer to	e your combination review your air
LOOK-UP:	If "K" = "Window" and "L" = "Ye If "K" = "Window" and "L" = "No If "K" = "Wall" and "L" = "Yes," If "K" = "Wall" and "L" = "No," t	o," then GOTO Table #	e#2 4	

NOTE TO PROGRAMMERS:

IF "K" = "Window" and "L" = "Yes,"
And
IF models selected begin with XH or XQ,
THEN
The Picture/Spec screen has to include the following:

"Your installation requires the purchase of a window installation kit.

Part Number 73XH900001 Price \$39.00

OR,

IF "K" = "Window" and "L" = "Yes,"
And
IF models selected begin with YH,
THEN,
The Picture/Spec screen has to include the following:

Your installation requires the purchase of a window installation kit.

Part Number 73YH900001

Price \$39.00

OR,

IF "K" = "Window" and "L" = "Yes,"
And
IF models selected begin with YH, and/or XH and/or XQ
THEN,
The Picture/Spec screen has to include the following:

"The YH model(s) requires the purchase of the following window installation kit: Part Number 73YH900001 Price \$39.00

The XH and XQ models require the purchase of the following window installation kit: Part Number 73XH900001 Price \$39.00

SELECT APPROPRIATE UNITS BASED ON BTU # 9 AND TABLE 2, 3, OR 4 GOTO PICTURE/SPEC FILE.

TABLE # 1:

No. 1808 Bit spent plane offers

Table A

	ZIP I	, Map
(Code Fa	ctor
	0 1000	8.0 8.0
	1999	8.0
	2000	8.0
	2999 3000	8.0 8.0
	3199	8.0
	3200	0.7 0.7
	3999 4000	0.7
	4999	0.7
	5000 5299	8.0 8.0
	5300	0.7
	5999	0.7
	6000 6999	8.0 8.0
	7000	0.9
	8999	0.9
IJ	10000 11999	0. 9 0.9
**************************************	12000	0.7
	12999 13000	0.7 0.8
2 223 2 223 2 223	14999	8.0
H	15000	8.0
	15999 16000	0.8 0.9
4	17999	0.9
	18000 18999	8.0 8.0
	19000	0.9
10	19999	0.9
	20000	1 1
		0.9
	20999 21000	0.9 0.75
	21999	0.75
	22000 24999	1 1
	25000	0.9
	26999	0.9
	27000 28399	1 1
	28400	0.9
	28999	0.9 1
	29000 29999	1
	30000	1
	31999 32000	1 0.975
	32999	0.975
	33000	0.95
	34999	0.95

```
35000
            1
36999
            ,1
37000
           <sup>,</sup> 1
37999
            1
 38000
           1.1
 38999
           1.1
 39000
          1.05
 39999
          1.05
 40000
          0.95
 42999
          0.95
           0.9
 43000
 45999
           0.9
 46000
           0.9
           0.9
 46999
             1
 47000
 47999
             1
 48000
           0.9
 48999
           0.9
 49000
          0.75
 49999
          0.75
  50000
             1
  51999
             1
52000
            0.9
52999
            0.9
__53000
            0.9
53999
            0.9
54000
           0.75
54999
           0.75
  55000
            0.9
  56999
            0.9
57000
           1.05
           1.05
  57999
58000
           0.95
           0.95
58999
              1
59000
1 59199
              1
            0.9
  59200
13
             0.9
   59599
             8.0
   59600
             8.0
   59999
             0.9
   60000
             0.9
   61999
               1
   62000
   62999
               1
   63000
               1
   65999
               1
   66000
               1
   66999
               1
             1.2
   67000
             1.2
   67999
              1.1
   68000
              1.1
   69999
   70000
               1
   70999
               1
              1.1
    71000
              1.1
    71999
    72000
              1.2
              1.2
1.2
    72999
    73000
    74999
              1.2
```

```
75000
           1.2
           1,2
 79999
           ı ٔ 1
 80000
             1
 81999
 82000
           0.9
           0.9
 82999
             1
 83000
 83999
             1
 84000
             1
 84999
             1
 85000
           1.4
           1.4
 85499
           0.9
  85500
           0.9
  86199
  86200
           1.25
           1.25
  86999
  87000
             1
  87999
              1
            1.1
  88000
            1.1
  88999
  89000
           1.25
  89299
           1.25
  89300
           0.85
89499
           0.85
  89500
              1
  89899
              1
89900
           0.85
89999
90000
           0.85
            8.0
90999
            8.0
91000
            1.1
91999
             1.1
  92000
            8.0
92199
             8.0
92200
             1.4
92399
             1.4
   92400
            1.25
ť.
   93099
            1.25
93100
             8.0
93199
             8.0
   93200
            1.25
   93999
94000
            1.25
             8.0
   94999
             8.0
            1.15
   95000
   95999
            1.15
   96000
             1.1
   96699
              1.1
   96700
               1
    96999
               1
    97000
            0.85
            0.85
    97999
    98000
              0.7
              0.7
    98599
    98600
             0.85
    98799
             0.85
    98800
                1
                1
    99499
    99500
              0.7
    99999
              0.7
```

TABLE # 2: Cooling Only Units

If BTU # 9 is	Select
3000 to 5200	UCA051B
	TCB051B
	TCA051B
•	
5201 to 7000	LCA061P
	UCB061B
	TCA061D
	PCA061D
7001 to 9000	UCD081B
	TCA081D
	TCA081P
	53SSB009-1
9001 to 11000	TCA101D
9001 to 11000	GCA101B
	53SSB009-1
	33000001
11001 to 13000	TCA121D
1	GCA121B
	GCA123B
200	XCB121E
	XCB121R
Market Product	462AJC012BA
À	DCA131G
in the second second	
13001 to 14000	DCA141D
44001 to 16500	DCA153D
-	462AJC015BA
	VOD102D
16501 to 19000	XCB183D
	XCB183E 462AJC018BA
	402AJC018BA
19001 to 22000	DCA213D
17001 to 22000	YCA213R
	462AJC021BA
	YCB213E
22001 to 25000	JCA243D

TABLE # 3: Through Wall Units

1	1 Culout
If BTU # 9 is	Select
3000 to 5200	UCA051B
5201 to 7000	UCB061B
7001 to 9000	UCD081B
9001 to 11000	GCA101B
11001 to 13000	GCA121B
	GCA123B XCB121E
	XCB121R
	462AJC012BA
	DCA131G
13001 to 14000	DCA141D
14001 to 16500	DCA153D
	462AJC015BA
46501 to 19000	XCB183D
(20) (20)	XCB183E
<u>.</u>	462AJC018BA
19001 to 22000	DCA213D
1 12	YCA213R
	462AJC021BA YCB213E
oe:	1002130
22001 to 25000	JCA243D
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
the state of the s	

Table # 4: Heating Units

	•
If BTU # 9 is	Select
3000 to 5200	N/A .
5201 to 7000	N/A
7001 to 9000	N/A
7001 10 7000	
9001 to 11000	XHC101D
3001 to 11000	XQB101D
	AOBIOID
11001 4- 12000	XHA123D
11001 to 13000	
	XQA123D
	7774 100D
13001 to 14000	XHA123D
	XQA123D
14001 to 16500	XHB153D
	XQB153D
16501 to 19000	XHB183D
2	XQB183D
minus comments	
19001 to 22000	YHB243D
22001 to 25000	YHB243D
- marry - marry - 1 2 3 - 1 3 1 - 1 3	
722 150	
OF COMMAND	•
of the control of the	
20 1 10 1	
UN STATE CONTROL OF THE CONTROL OF	
are grown and a second and	